



技术要求：

- A端子为1.25间距6孔端子
参考型号：
 - MOLEX 510210600
 - HCTL(华灿天禄) HC-1.25-6Y
 - BOOMELE(博穆精密)- 1.25T-6Y
- 信号线使用30AWG硅胶线，要求使用排线；
- 端子连接方式：反向（针脚顺序相同）

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 WESTWOOD ROBOTICS CORPORATION.
 ANY REPRODUCTION IN PART OR AS A
 WHOLE WITHOUT THE WRITTEN PERMISSION
 OF WESTWOOD ROBOTICS CORPORATION
 IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN mm		NAME		DATE		DO NOT SCALE DRAWING	
		TOLERANCE:		DRAWN					
		x ±0.1		CHECKED					
		x.x ±0.05		ENG APPR.					
		x.xx ±0.01		MFG APPR.					
		ANGLES ±0.2°		Q.A.					
		MATERIAL		FINISH					
NEXT ASSY		USED ON		CLEAN&DEBUR				BR01-BEAR_SIGNAL_02	
APPLICATION		Quantity		1				SIZE A4 DWG. NO. BR01-SC-B2B-02 REV. A	
						SCALE:2:1		WEIGHT: SHEET 1 OF 1	